


LFP1100T SERIES -1060T


Demand / Delivery Pump



Flow Curve



Temperature Rise @ Current 1.55A



Performance data and curves

Data were tested at inlet pressure of 0PSI, ambient temperature and water temperature of 25°C, and voltage of 24V DC. The above is the test data of 3/8" pipe. If other pipe sizes are used, the test data will be different.

Temperature rise curve


The temperature rise curve is measured by the ambient temperature of 25°C, the inlet pressure of 0PSI, and the working pressure of 70PSI. In order to ensure the safety of the motor, the housing temperature exceeds approximately 73 °C, and the thermal protector is disconnected to cool the motor. The motor will be continuous working when the actual temperature rise of the motor is lower than the thermal protection disconnection temperature. All performance data and temperature curves are approximate, and actual conditions will vary with ambient conditions such as temperature.

Performance parameter

Discharge Pressure /PSI	Flow Rate /GPM	Flow Rate /LPM	Current /A
0	0.60	2.27	0.61
10	0.57	2.16	0.74
20	0.55	2.08	0.88
30	0.52	1.97	1.01
40	0.50	1.89	1.14
50	0.48	1.82	1.27
60	0.45	1.70	1.41
70	0.43	1.63	1.54

Shut-off pressure for selection

Selection	Rated voltage	Inlet Water Pressure	Working Flow Rate	Working Current	Suction	Shut-off Pressure	Maximum current	Connection
LFP1060T-30070	24V DC	0PSI	0.6GPM	≤1.0A	≥2M	70PSI	≤1.9A	3/8" side female quick connector NPT3/8 Screw thread
LFP1060T-30060						60PSI	≤1.8A	
LFP1060T-30050						50PSI	≤1.7A	
LFP1060T-30040						40PSI	≤1.5A	
LFP1060T-30030						30PSI	≤1.4A	




/// Demand / Delivery Pump

LFP1100T SERIES -1075T


Demand / Delivery Pump



Flow Curve



Temperature Rise @ Current 1.8A



Performance data and curves

Data were tested at inlet pressure of 0PSI, ambient temperature and water temperature of 25°C, and voltage of 24V DC. The above is the test data of 3/8" pipe. If other pipe sizes are used, the test data will be different.

Temperature rise curve


The temperature rise curve is measured by the ambient temperature of 25°C, the inlet pressure of 0PSI, and the working pressure of 70PSI. In order to ensure the safety of the motor, the housing temperature exceeds approximately 73 °C, and the thermal protector is disconnected to cool the motor. The motor will be continuous working when the actual temperature rise of the motor is lower than the thermal protection disconnection temperature. All performance data and temperature curves are approximate, and actual conditions will vary with ambient conditions such as temperature.

Performance parameter

Discharge Pressure /PSI	Flow Rate /GPM	Flow Rate /LPM	Current /A
0	0.75	2.84	0.68
10	0.72	2.73	0.83
20	0.69	2.61	0.99
30	0.66	2.50	1.15
40	0.63	2.39	1.3
50	0.60	2.27	1.46
60	0.57	2.16	1.61
70	0.54	2.05	1.77

Shut-off pressure for selection

Selection	Rated voltage	Inlet Water Pressure	Working Flow Rate	Working Current	Suction	Shut-off Pressure	Maximum current	Connection
LFP1075T-30070	24V DC	0PSI	0.75GPM	≤1.1A	≥2M	70PSI	≤2.1A	3/8" side female quick connector NPT3/8 Screw thread
LFP1075T-30060						60PSI	≤2.0A	
LFP1075T-30050						50PSI	≤1.8A	
LFP1075T-30040						40PSI	≤1.7A	
LFP1075T-30030						30PSI	≤1.5A	




LFP1100T SERIES -1085T


Demand / Delivery Pump



Flow Curve



Temperature Rise @ Current 2.1A



Performance data and curves

Data were tested at inlet pressure of 0PSI, ambient temperature and water temperature of 25°C, and voltage of 24V DC. The above is the test data of 3/8" pipe. If other pipe sizes are used, the test data will be different.

Temperature rise curve


The temperature rise curve is measured by the ambient temperature of 25°C, the inlet pressure of 0PSI, and the working pressure of 70PSI. In order to ensure the safety of the motor, the housing temperature exceeds approximately 73 °C, and the thermal protector is disconnected to cool the motor. The motor will be continuous working when the actual temperature rise of the motor is lower than the thermal protection disconnection temperature. All performance data and temperature curves are approximate, and actual conditions will vary with ambient conditions such as temperature.

Performance parameter

Discharge Pressure /PSI	Flow Rate /GPM	Flow Rate /LPM	Current /A
0	0.85	3.22	0.90
10	0.82	3.11	1.07
20	0.79	3.0	1.24
30	0.76	2.89	1.41
40	0.73	2.78	1.59
50	0.71	2.67	1.76
60	0.68	2.56	1.93
70	0.65	2.45	2.10

Shut-off pressure for selection

Selection	Rated voltage	Inlet Water Pressure	Working Flow Rate	Working Current	Suction	Shut-off Pressure	Maximum current	Connection
LFP1085T-30070	24V DC	0PSI	0.85GPM	≤1.3A	≥2M	70PSI	≤2.5A	3/8" side female quick connector NPT3/8 Screw thread
LFP1085T-30060						60PSI	≤2.3A	
LFP1085T-30050						50PSI	≤2.1A	
LFP1085T-30040						40PSI	≤1.9A	
LFP1085T-30030						30PSI	≤1.8A	




/// Demand / Delivery Pump

LFP1100T SERIES -1100T


Demand / Delivery Pump



Flow Curve



Temperature Rise @ Current 2.5A



Performance data and curves

Data were tested at inlet pressure of 0PSI, ambient temperature and water temperature of 25°C, and voltage of 24V DC. The above is the test data of 3/8" pipe. If other pipe sizes are used, the test data will be different.

Temperature rise curve


The temperature rise curve is measured by the ambient temperature of 25°C, the inlet pressure of 0PSI, and the working pressure of 70PSI. In order to ensure the safety of the motor, the housing temperature exceeds approximately 73 °C, and the thermal protector is disconnected to cool the motor. The motor will be continuous working when the actual temperature rise of the motor is lower than the thermal protection disconnection temperature. All performance data and temperature curves are approximate, and actual conditions will vary with ambient conditions such as temperature.

Performance parameter

Discharge Pressure /PSI	Flow Rate /GPM	Flow Rate /LPM	Current /A
0	1.0	3.79	1.00
10	0.97	3.67	1.22
20	0.94	3.56	1.42
30	0.91	3.44	1.63
40	0.88	3.32	1.84
50	0.85	3.21	2.04
60	0.82	3.09	2.25
70	0.78	2.97	2.46

Shut-off pressure for selection

Selection	Rated voltage	Inlet Water Pressure	Working Flow Rate	Working Current	Suction	Shut-off Pressure	Maximum current	Connection
LFP1100T-30070	24V DC	0PSI	1.0GPM	≤1.4A	≥2M	70PSI	≤2.8A	3/8" side female quick connector NPT3/8 Screw thread
LFP1100T-30060						60PSI	≤2.6A	
LFP1100T-30050						50PSI	≤2.4A	
LFP1100T-30040						40PSI	≤2.2A	
LFP1100T-30030						30PSI	≤2.0A	




LFP1150T SERIES -1115T


Demand / Delivery Pump



Flow Curve



Temperature Rise @ Current 2.9A



Performance data and curves

Data were tested at inlet pressure of 0PSI, ambient temperature and water temperature of 25°C, and voltage of 24V DC. The above is the test data of 3/8" pipe. If other pipe sizes are used, the test data will be different.

Temperature rise curve


The temperature rise curve is measured by the ambient temperature of 25°C, the inlet pressure of 0PSI, and the working pressure of 70PSI. In order to ensure the safety of the motor, the housing temperature exceeds approximately 73 °C, and the thermal protector is disconnected to cool the motor. The motor will be continuous working when the actual temperature rise of the motor is lower than the thermal protection disconnection temperature. All performance data and temperature curves are approximate, and actual conditions will vary with ambient conditions such as temperature.

Performance parameter

Discharge Pressure /PSI	Flow Rate /GPM	Flow Rate /LPM	Current /A
0	1.15	4.35	1.42
10	1.12	4.24	1.58
20	1.09	4.13	1.79
30	1.06	4.02	2.01
40	1.03	3.9	2.22
50	1.00	3.79	2.44
60	0.97	3.68	2.66
70	0.94	3.57	2.9

Shut-off pressure for selection

Selection	Rated voltage	Inlet Water Pressure	Working Flow Rate	Working Current	Suction	Shut-off Pressure	Maximum current	Connection
LFP1115T-30070	24V DC	0PSI	1.15GPM	≤1.6A	≥2M	70PSI	≤3.3A	3/8" side female quick connector NPT3/8 Screw thread
LFP1115T-30060						60PSI	≤3.1A	
LFP1115T-30050						50PSI	≤2.8A	
LFP1115T-30040						40PSI	≤2.6A	
LFP1115T-30030						30PSI	≤2.4A	




Demand / Delivery Pump

LFP1150T SERIES -1125T


Demand / Delivery Pump



Flow Curve



Temperature Rise @ Current 3.3A



Performance data and curves

Data were tested at inlet pressure of 0PSI, ambient temperature and water temperature of 25°C, and voltage of 24V DC. The above is the test data of 3/8" pipe. If other pipe sizes are used, the test data will be different.

Temperature rise curve


The temperature rise curve is measured by the ambient temperature of 25°C, the inlet pressure of 0PSI, and the working pressure of 70PSI. In order to ensure the safety of the motor, the housing temperature exceeds approximately 73 °C, and the thermal protector is disconnected to cool the motor. The motor will be continuous working when the actual temperature rise of the motor is lower than the thermal protection disconnection temperature. All performance data and temperature curves are approximate, and actual conditions will vary with ambient conditions such as temperature.

Performance parameter

Discharge Pressure /PSI	Flow Rate /GPM	Flow Rate /LPM	Current /A
0	1.25	4.73	1.62
10	1.22	4.61	1.8
20	1.19	4.49	2.04
30	1.15	4.37	2.28
40	1.12	4.24	2.53
50	1.09	4.12	2.77
60	1.06	4.00	3.02
70	1.03	3.88	3.26

Shut-off pressure for selection

Selection	Rated voltage	Inlet Water Pressure	Working Flow Rate	Working Current	Suction	Shut-off Pressure	Maximum current	Connection
LFP1125T-30070	24V DC	0PSI	1.25GPM	≤1.9A	≥2M	70PSI	≤3.7A	3/8" side female quick connector NPT3/8 Screw thread
LFP1125T-30060						60PSI	≤3.4A	
LFP1125T-30050						50PSI	≤3.2A	
LFP1125T-30040						40PSI	≤2.9A	
LFP1125T-30030						30PSI	≤2.7A	




LFP1150T SERIES -1140T


Demand / Delivery Pump



Flow Curve



Temperature Rise @ Current 3.6A



Performance data and curves

Data were tested at inlet pressure of 0PSI, ambient temperature and water temperature of 25°C, and voltage of 24V DC. The above is the test data of 3/8" pipe. If other pipe sizes are used, the test data will be different.

Temperature rise curve


The temperature rise curve is measured by the ambient temperature of 25°C, the inlet pressure of 0PSI, and the working pressure of 70PSI. In order to ensure the safety of the motor, the housing temperature exceeds approximately 73 °C, and the thermal protector is disconnected to cool the motor. The motor will be continuous working when the actual temperature rise of the motor is lower than the thermal protection disconnection temperature. All performance data and temperature curves are approximate, and actual conditions will vary with ambient conditions such as temperature.

Performance parameter

Discharge Pressure /PSI	Flow Rate /GPM	Flow Rate /LPM	Current /A
0	1.40	5.30	1.76
10	1.37	5.17	2.02
20	1.33	5.03	2.28
30	1.29	4.90	2.54
40	1.26	4.77	2.79
50	1.22	4.63	3.1
60	1.19	4.50	3.31
70	1.15	4.37	3.57

Shut-off pressure for selection

Selection	Rated voltage	Inlet Water Pressure	Working Flow Rate	Working Current	Suction	Shut-off Pressure	Maximum current	Connection
LFP1140T-30070	24V DC	0PSI	1.40GPM	≤2.2A	≥2M	70PSI	≤4.0A	3/8" side female quick connector NPT3/8 Screw thread
LFP1140T-30060						60PSI	≤3.7A	
LFP1140T-30050						50PSI	≤3.5A	
LFP1140T-30040						40PSI	≤3.2A	
LFP1140T-30030						30PSI	≤3.0A	




Demand / Delivery Pump

LFP1150T SERIES -1150T


Demand / Delivery Pump



Flow Curve



Temperature Rise @ Current 4.0A



Performance data and curves

Data were tested at inlet pressure of 0PSI, ambient temperature and water temperature of 25°C, and voltage of 24V DC. The above is the test data of 3/8" pipe. If other pipe sizes are used, the test data will be different.

Temperature rise curve

The temperature rise curve is measured by the ambient temperature of 25°C, the inlet pressure of 0PSI, and the working pressure of 70PSI. In order to ensure the safety of the motor, the housing temperature exceeds approximately 73 °C, and the thermal protector is disconnected to cool the motor. The motor will be continuous working when the actual temperature rise of the motor is lower than the thermal protection disconnection temperature. All performance data and temperature curves are approximate, and actual conditions will vary with ambient conditions such as temperature.

Performance parameter

Discharge Pressure /PSI	Flow Rate /GPM	Flow Rate /LPM	Current /A
0	1.50	5.68	2.0
10	1.46	5.53	2.11
20	1.42	5.38	2.4
30	1.38	5.24	2.69
40	1.34	5.09	2.98
50	1.31	4.98	3.3
60	1.27	4.79	3.56
70	1.23	4.65	3.9

Shut-off pressure for selection

Selection	Rated voltage	Inlet Water Pressure	Working Flow Rate	Working Current	Suction	Shut-off Pressure	Maximum current	Connection
LFP1150T-30070	24V DC	0PSI	1.50GPM	≤2.3A	≥2M	70PSI	≤4.3A	3/8" side female quick connector NPT3/8 Screw thread
LFP1150T-30060						60PSI	≤4.0A	
LFP1150T-30050						50PSI	≤3.7A	
LFP1150T-30040						40PSI	≤3.4A	
LFP1150T-30030						30PSI	≤3.1A	

